Safety Data cording to Federa ter / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations Revision date: 09/16/2013

Version:

SECTION 1: Identification of the sub	stance	/mixture and of the company/u	Indertaking	
1.1. Product identifier			Ĭ	
Product form	: Mixtu	res		
Product name.	: TECH	H SELECT POE OIL CHARGE 6/4oz		
Product code	: 4005	9026		
1.2. Relevant identified uses of the subs	tance or	mixture and uses advised against		
Use of the substance/mixture	: FOLL	OW LABEL DIRECTIONS		
1.3. Details of the supplier of the safety of	data she	et		
FOUR SEASONS MFG CO. 1801 WATERS RIDGE DR. LEWISVILLE, TX 75057				
1.4. Emergency telephone number				
Emergency number	: CHEI	MTREC 24 Hour 1-800-424-9300		
SECTION 2: Hazards identification				
2.1. Classification of the substance or m	ixture			
Classification (GHS-US)				
Compressed gas H280				
2.2. Label elements				
GHS-US labeling				
Hazard pictograms (GHS-US)	:	\wedge		
Signal word (GHS-US) Hazard statements (GHS-US) Precautionary statements (GHS-US)	: Warn : H280 : P410	 Contains gas under pressure; may exp +P403 - Protect from sunlight. Store in a 	well-ventilated	•
		 Pressurized container: Do not pierce o Do not expose to temperatures exceed 		
2.3. Other hazards				
Other hazards not contributing to the classification	: Conta heate	act with liquid may cause cold burns/frosi ad.	tbite. Contains g	gas under pressure; may explode if
2.4. Unknown acute toxicity (GHS-US)				
No data available				
SECTION 3: Composition/informatio	n on in	gredients		
3.1. Substances				
Not applicable				
3.2. Mixtures				
Name		Product identifier	%	Classification (GHS-US)
1,1,1,2-tetrafluoroethane		(CAS No) 811-97-2	50 - 70	Compressed gas, H280
		(CAS No) Proprietary	30 - 50	Not classified
PROPRIETARY INHIBITOR PACKAGE		(CAS No) Proprietary	5 - 10	Not classified
SECTION 4: First aid measures				
4.1. Description of first aid measures				
First-aid measures general		r give anything by mouth to an unconscie v the label where possible).	ous person. If yo	ou feel unwell, seek medical advice
First-aid measures after inhalation	: Assu	re fresh air breathing. Allow the victim to	rest.	
First-aid measures after skin contact		ove affected clothing and wash all expose water rinse.	ed skin area wit	h mild soap and water, followed by
First-aid measures after eye contact	: Rinse persis	e immediately with plenty of water. Obtain st.	n medical attent	ion if pain, blinking or redness
First-aid measures after ingestion	•	e mouth. Do NOT induce vomiting. Obtain	n emergency m	edical attention.
16/09/2013	EN (Eng	glish US)		1/6

16/09/2013

Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

4.2. Most important symptoms and e	effects, both acute and delayed
Symptoms/injuries	: Not expected to present a significant hazard under anticipated conditions of normal use.
4.3. Indication of any immediate me	dical attention and special treatment needed
No additional information available	
SECTION 5: Firefighting measure	es
5.1. Extinguishing media	
suitable extinguishing media	: Foam. Dry powder. Carbon dioxide. Water spray. Sand.
Unsuitable extinguishing media	: Do not use a heavy water stream.
5.2. Special hazards arising from the	e substance or mixture
No additional information available	
5.3. Advice for firefighters	
Firefighting instructions	: Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Avoid (reject) fire-fighting water to enter environment.
Protection during firefighting	: Do not enter fire area without proper protective equipment, including respiratory protection.
Other information	: NFPA Aerosol Level 1.
SECTION 6: Accidental release n	neasures
	e equipment and emergency procedures
6.1.1. For non-emergency personnel	
Emergency procedures	: Evacuate unnecessary personnel.
0 7.1	
6.1.2. For emergency responders	
Protective equipment	: Equip cleanup crew with proper protection.
Emergency procedures	: Ventilate area.
6.2. Environmental precautions	No 1964 and the Million Million to the second second by second and
	Notify authorities if liquid enters sewers or public waters.
6.3. Methods and material for contain	
Methods for cleaning up	: Store away from other materials.
6.4. Reference to other sections	
See Heading 8. Exposure controls and perso	onal protection.
SECTION 7: Handling and storag	e
7.1. Precautions for safe handling	
Precautions for safe handling	Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapor.
7.2. Conditions for safe storage, inc	
Storage conditions	: Keep only in the original container in a cool, well ventilated place away from : Keep container closed when not in use.
Incompatible products	: Strong bases. Strong acids.
Incompatible materials	: Sources of ignition. Direct sunlight.
Storage area	: Store in a well-ventilated place.
7.3. Specific end use(s)	
Follow Label Directions.	
SECTION 8: Exposure controls/p	ersonal protection
8.1. Control parameters	
8.2. Exposure controls	
Personal protective equipment	: Avoid all unnecessary exposure.
Hand protection	: Wear protective gloves.
Eye protection	: Chemical goggles or safety glasses.
Respiratory protection	: Wear appropriate mask.
Other information	: Do not eat, drink or smoke during use.
SECTION 9: Physical and chemic	cal properties
9.1. Information on basic physical a	
Physical state	: Gas

EN (English US)

2/6

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Appearance	: Gas.
Molecular mass	: 102.03 g/mol
Color	: Colourless.
Odor	: Ether-like odour.
Odor threshold	: No data available
рН	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Melting point	: -101 °C
Freezing point	: No data available
Boiling point	: -26 °C LOWEST COMPONENT
Flash point	: > 149 ℃
Critical temperature	: 101 °C
Self ignition temperature	: > 743 °C
Decomposition temperature	: 368 °C
Flammability (solid, gas)	: No data available
Vapor pressure	: 5720 hPa
Critical pressure	: 40560 hPa
Relative vapor density at 20 °C	: 3.52 (20 °C)
Relative density	: 1.2 (-27 °C)
Density	: 1206 kg/m³ (-27 °C)
Solubility	: Poorly soluble in water. Soluble in ethanol. Soluble in ether. Soluble in hexane. Water: 0.15 g/100ml (25 °C)
Log Pow	: 1.06 (OECD 107: Partition Coefficient (n-octanol/water): Shake Flask Method)
Log Kow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available
Explosive limits	: No data available
9.2. Other information	
VOC content	: 0%
Gas group	: Compressed gas
SECTION 10: Stability and reactivi	fs/
10.1. Reactivity	

10.1. Reactivity No additional information available 10.2. **Chemical stability** Not established. 10.3. Possibility of hazardous reactions Not established. **Conditions to avoid** 10.4. Direct sunlight. Extremely high or low temperatures. 10.5. Incompatible materials Strong acids. Strong bases. 10.6. Hazardous decomposition products fume. Carbon monoxide. Carbon dioxide. **SECTION 11: Toxicological information** 11.1. Information on toxicological effects

Acute toxicity

: Not classified

1,1,1,2-tetrafluoroethane (811-97-2)		
LC50 inhalation rat (mg/l)	> 2000 mg/l/4h (Rat)	
LC50 inhalation rat (ppm)	> 359300 ppm/4h (Rat)	
Skin corrosion/irritation	: Not classified	
Serious eye damage/irritation	: Not classified	
16/09/2013	EN (English US)	3/6

Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classifiedBased on available data, the classification criteria are not met
Carcinogenicity	: Not classified
Reproductive toxicity Specific target organ toxicity (single exposure)	: Not classifiedBased on available data, the classification criteria are not met : Not classified
Specific target organ toxicity (repeated exposure)	: Not classifiedBased on available data, the classification criteria are not met
Aspiration hazard	: Not classifiedBased on available data, the classification criteria are not met
Potential Adverse human health effects and symptoms	: Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

12.1. Toxicity

1,1,1,2-tetrafluoroethane (811-97-2)		
LC50 fish 1	450 mg/l 96 h; Salmo gairdneri (Oncorhynchus mykiss)	
EC50 Daphnia 1	980 mg/l (48 h; Daphnia magna)	
	900 mg/r (40 m, Dapinna magna)	
12.2. Persistence and degradability		
TECH SELECT POE OIL CHARGE 6/4oz		
Persistence and degradability	Not established.	
Zerol Ester 68 (Proprietary)		
Persistence and degradability	Not established.	
PROPRIETARY INHIBITOR PACKAGE (Proprie	etary)	
Persistence and degradability	Not established.	
1,1,1,2-tetrafluoroethane (811-97-2)		
Persistence and degradability	Not readily biodegradable in water.	
12.3. Bioaccumulative potential		
TECH SELECT POE OIL CHARGE 6/4oz		
Log Pow	1.06 (OECD 107: Partition Coefficient (n-octanol/water): Shake Flask Method)	
Bioaccumulative potential	Not established.	
Zerol Ester 68 (Proprietary)		
Bioaccumulative potential	Not established.	
PROPRIETARY INHIBITOR PACKAGE (Proprietary)		
Bioaccumulative potential	Not established.	
1,1,1,2-tetrafluoroethane (811-97-2)		
BCF other aquatic organisms 1	5 - 58 (Estimated value)	
Log Pow	1.06 (OECD 107: Partition Coefficient (n-octanol/water): Shake Flask Method)	
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).	

No additional information available

12.5. Other adverse effects

Other information

: Avoid release to the environment.

SECTION 13: Disposal considerations		
13.1. Waste treatment methods		
Waste disposal recommendations	: Dispose in a safe manner in accordance with local/national regulations.	
Ecology - waste materials	: Avoid release to the environment.	

Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 14: Tran	nsport information
In accordance with ADF	R / RID / ADNR / IMDG / ICAO / IATA
US DOT (ground):	UN1078, Refrigerant gases, n.o.s., 2.2, Limited Quantity
ICAO/IATA (air):	UN1078, Refrigerant gases, n.o.s., 2.2, Limited Quantity
IMO/IMDG (water):	UN1078, Refrigerant gases, n.o.s., 2, Limited Quantity
Special Provisions:	T50 - When portable tank instruction T50 is referenced in Column (7) of the 172.101 Table, the applicable liquefied compressed gases are authorized to be transported in portable tanks in accordance with the requirements of 173.313 of this subchapter.
14.2. UN proper s	hipping name

	14.2. On proper shipping name	
Classes 1 1 1 1 Hazard labels (DOT) : 2.2 - Non-flammable compressed gas DOT Symbols : G - Identifies PSN requiring a technical name DOT Special Provisions (49 CFR 172.102) : T50 - When portable tank instruction T50 is referenced in Column (7) of the 172.101 Table applicable liquefied compressed gases are authorized to be transported in portable tanks in accordance with the requirements of 173.313 of this subchapter. DOT Packaging Non Bulk (49 CFR 173.xxx) : 304 DOT Packaging Bulk (49 CFR 173.xxx) : 304 DOT Packaging Non Bulk (49 CFR 173.xxx) : 314;315 14.3. Additional information : No supplementary information available. Overland transport No supplementary information available. No additional information available : A - The material may be stowed 'on deck'' or 'under deck'' on a cargo vessel and on a passenger vessel. Air transport DOT Quantity Limitations Passenger aircraft/rail : 75 kg DOT Quantity Limitations Cargo aircraft only (49 : 150 kg SECTION 15: Regulatory information : 150 kg TGRA Section 311/312 Hazard Classes Immediate (acute) health hazard Sudden release of pressure hazard Sudden release of pressure hazard	DOT Proper Shipping Name	: Refrigerant gases, n.o.s.
DOT Symbols : G - Identifies PSN requiring a technical name DOT Special Provisions (49 CFR 172.102) : T50 - When portable tank instruction T50 is referenced in Column (7) of the 172.101 Table applicable liquefied compressed gases are authorized to be transported in portable tank instruction T50 is referenced in Column (7) of the 172.101 Table applicable liquefied compresses gases are authorized to be transported in portable tanks in accordance with the requirements of 173.313 of this subchapter. DOT Packaging Non Bulk (49 CFR 173.xxx) : 306 DOT Packaging Non Bulk (49 CFR 173.xxx) : 304 DOT Packaging Bulk (49 CFR 173.xxx) : 304 DOT Packaging Bulk (49 CFR 173.xxx) : 304 DOT Packaging Bulk (49 CFR 173.xxx) : 304 Other information : No supplementary information available. Overland transport No additional information available Transport by sea : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel. DoT Quantity Limitations Passenger aircraft/rail : 75 kg OT Quantity Limitations Cargo aircraft (rail) : 75 kg SECTION 15: Regulatory information : 150 kg TECH SELECT POE OIL CHARGE 6462 SARA Section 311/312 Hazard Classes Sudden release of pressure hazard : Immediate (acute) heath hazard suden release of pressure hazard 1,		: 2.2 - Class 2.2 - Non-flammable compressed gas 49 CFR 173.115
DOT Special Provisions (49 CFR 172.102) : T50 - When portable tank instruction T50 is referenced in Column (7) of the 172.101 Table applicable liquefied compressed gases are authorized to be transported in portable tanks accordance with the requirements of 173.313 of this subchapter. DOT Packaging Exceptions (49 CFR 173.xxx) : 306 DOT Packaging Non Bulk (49 CFR 173.xxx) : 304 DOT Packaging Bulk (49 CFR 173.xxx) : 314;315 14.3. Additional information	Hazard labels (DOT)	: 2.2 - Non-flammable compressed gas
DOT Special Provisions (49 CFR 172.102) : T50 - When portable tank instruction T50 is referenced in Column (7) of the 172.101 Table applicable liquefied compressed gases are authorized to be transported in portable tanks accordance with the requirements of 173.313 of this subchapter. DOT Packaging Exceptions (49 CFR 173.xxx) : 306 DOT Packaging Non Bulk (49 CFR 173.xxx) : 304 DOT Packaging Buk (49 CFR 173.xxx) : 314;315 14.3. Additional information : No supplementary information available. Overland transport No additional information available Transport by sea : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel. Air transport : 75 kg DOT Quantity Limitations Passenger aircraft/rail : 75 kg CFR 173.27) : 150 kg SECTION 15: Regulatory information : 150 kg TECH SELECT POE OIL CHARGE 6/4oz : SARA Section 311/312 Hazard Classes SARA Section 311/312 Hazard Classes Immediate (acute) health hazard Sudden release of pressure hazard 1,1,2-tetrafluoroethane (811-97-2) :		
applicable liquefied compressed gases are authorized to be transported in portable tanks i accordance with the requirements of 173.313 of this subchapter. DOT Packaging Exceptions (49 CFR 173.xxx) : 304 DOT Packaging Non Bulk (49 CFR 173.xxx) : 314;315 14.3. Additional information Other information : No supplementary information available. Overland transport No additional information available Transport by sea DOT Vessel Stowage Location : A - The material may be stowed 'on deck" or "under deck" on a cargo vessel and on a passenger vessel. Air transport DOT Quantity Limitations Passenger aircraft/rail : 75 kg (49 CFR 173.27) DOT Quantity Limitations Cargo aircraft only (49 : 150 kg SECTION 15: Regulatory information 15.1. US Federal regulations TECH SELECT POE OIL CHARGE 6/40z SARA Section 311/312 Hazard Classes Immediate (acute) health hazard Sudden release of pressure hazard 1,1,2-tetrafluoroethane (811-97-2)	DOT Symbols	: G - Identifies PSN requiring a technical name
DOT Packaging Non Bulk (49 CFR 173.xxx) : 304 DOT Packaging Bulk (49 CFR 173.xxx) : 314;315 14.3. Additional information Other information : No supplementary information available. Overland transport No additional information available Transport by sea DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel. Air transport DOT Quantity Limitations Passenger aircraft/rail : 75 kg (49 CFR 173.27) DOT Quantity Limitations Cargo aircraft only (49 : 150 kg CFR 175.75) SECTION 15: Regulatory information 15.1. US Federal regulations TECH SELECT POE OIL CHARGE 6/40z SARA Section 311/312 Hazard Classes Immediate (acute) health hazard Sudden release of pressure hazard 1,1,2-tetrafluoroethane (811-97-2)	DOT Special Provisions (49 CFR 172.102)	: T50 - When portable tank instruction T50 is referenced in Column (7) of the 172.101 Table, the applicable liquefied compressed gases are authorized to be transported in portable tanks in accordance with the requirements of 173.313 of this subchapter.
DOT Packaging Bulk (49 CFR 173.xxx) : 314;315 14.3. Additional information	DOT Packaging Exceptions (49 CFR 173.xxx)	: 306
14.3. Additional information Other information : No supplementary information available. Overland transport No additional information available Transport by sea DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel. Air transport DOT Quantity Limitations Passenger aircraft/rail : 75 kg (49 CFR 173.27) DOT Quantity Limitations Cargo aircraft only (49) : 150 kg CFR 175.75) SECTION 15: Regulatory information 15.1. US Federal regulations TECH SELECT POE OIL CHARGE 6/40z SARA Section 311/312 Hazard Classes Immediate (acute) health hazard Sudden release of pressure hazard 1,1,1,2-tetrafluoroethane (811-97-2)	DOT Packaging Non Bulk (49 CFR 173.xxx)	: 304
Other information : No supplementary information available. Overland transport No additional information available Transport by sea DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel. Air transport DOT Quantity Limitations Passenger aircraft/rail : 75 kg May CFR 173.27) DOT Quantity Limitations Cargo aircraft only (49) : 150 kg SECTION 15: Regulatory information 151. US Federal regulations TECH SELECT POE OIL CHARGE 6/40z Immediate (acute) health hazard Sudden release of pressure hazard AI,1,2-tetrafluoroethane (811-97-2) Immediate (acute) health hazard Sudden release of pressure hazard	DOT Packaging Bulk (49 CFR 173.xxx)	: 314;315
Overland transport No additional information available Transport by sea DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel. Air transport DOT Quantity Limitations Passenger aircraft/rail : 75 kg (49 CFR 173.27)	14.3. Additional information	
No additional information available Transport by sea DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel. Air transport DOT Quantity Limitations Passenger aircraft/rail : 75 kg (49 CFR 173.27) DOT Quantity Limitations Cargo aircraft only (49 : 150 kg CFR 175.75) SECTION 15: Regulatory information 15.1. US Federal regulations TECH SELECT POE OIL CHARGE 6/40z SARA Section 311/312 Hazard Classes Immediate (acute) health hazard Sudden release of pressure hazard 1,1,1,2-tetrafluoroethane (811-97-2)	Other information	: No supplementary information available.
No additional information available Transport by sea DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel. Air transport DOT Quantity Limitations Passenger aircraft/rail : 75 kg (49 CFR 173.27) DOT Quantity Limitations Cargo aircraft only (49 : 150 kg CFR 175.75) SECTION 15: Regulatory information 15.1. US Federal regulations TECH SELECT POE OIL CHARGE 6/40z SARA Section 311/312 Hazard Classes Immediate (acute) health hazard Sudden release of pressure hazard 1,1,1,2-tetrafluoroethane (811-97-2)		
Transport by sea DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel. Air transport DOT Quantity Limitations Passenger aircraft/rail : 75 kg DOT Quantity Limitations Cargo aircraft only (49 : 150 kg : 150 kg CFR 175.75) : SECTION 15: Regulatory information 15.1. US Federal regulations : TECH SELECT POE OIL CHARGE 6/4oz SARA Section 311/312 Hazard Classes Immediate (acute) health hazard Sudden release of pressure hazard 1,1,1,2-tetrafluoroethane (811-97-2) : Immediate (acute) health hazard Sudden release of pressure hazard	Overland transport	
DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel. Air transport DOT Quantity Limitations Passenger aircraft/rail : 75 kg (49 CFR 173.27) DOT Quantity Limitations Cargo aircraft only (49 : 150 kg CFR 175.75) SECTION 15: Regulatory information 15.1. US Federal regulations TECH SELECT POE OIL CHARGE 6/40Z SARA Section 311/312 Hazard Classes Immediate (acute) health hazard Sudden release of pressure hazard 1,1,1,2-tetrafluoroethane (811-97-2)	No additional information available	
Air transport DOT Quantity Limitations Passenger aircraft/rail : 75 kg (49 CFR 173.27) DOT Quantity Limitations Cargo aircraft only (49 : 150 kg CFR 175.75) SECTION 15: Regulatory information 15.1. US Federal regulations TECH SELECT POE OIL CHARGE 6/4oz SARA Section 311/312 Hazard Classes Immediate (acute) health hazard Sudden release of pressure hazard 1,1,1,2-tetrafluoroethane (811-97-2)	Transport by sea	
DOT Quantity Limitations Passenger aircraft/rail : 75 kg (49 CFR 173.27) DOT Quantity Limitations Cargo aircraft only (49 : 150 kg CFR 175.75) SECTION 15: Regulatory information 15.1. US Federal regulations TECH SELECT POE OIL CHARGE 6/4oz SARA Section 311/312 Hazard Classes Immediate (acute) health hazard Sudden release of pressure hazard 1,1,1,2-tetrafluoroethane (811-97-2)	DOT Vessel Stowage Location	
(49 CFR 173.27) DOT Quantity Limitations Cargo aircraft only (49 : 150 kg CFR 175.75) SECTION 15: Regulatory information 15.1. US Federal regulations TECH SELECT POE OIL CHARGE 6/4oz SARA Section 311/312 Hazard Classes Immediate (acute) health hazard Sudden release of pressure hazard 1,1,1,2-tetrafluoroethane (811-97-2)	Air transport	
CFR 175.75) SECTION 15: Regulatory information 15.1. US Federal regulations TECH SELECT POE OIL CHARGE 6/4oz SARA Section 311/312 Hazard Classes Immediate (acute) health hazard Sudden release of pressure hazard 1,1,1,2-tetrafluoroethane (811-97-2)		: 75 kg
15.1. US Federal regulations TECH SELECT POE OIL CHARGE 6/4oz SARA Section 311/312 Hazard Classes Immediate (acute) health hazard Sudden release of pressure hazard 1,1,1,2-tetrafluoroethane (811-97-2)		: 150 kg
15.1. US Federal regulations TECH SELECT POE OIL CHARGE 6/4oz SARA Section 311/312 Hazard Classes Immediate (acute) health hazard Sudden release of pressure hazard 1,1,1,2-tetrafluoroethane (811-97-2)	SECTION 15: Pogulatory information	
TECH SELECT POE OIL CHARGE 6/4oz SARA Section 311/312 Hazard Classes Immediate (acute) health hazard Sudden release of pressure hazard 1,1,1,2-tetrafluoroethane (811-97-2)		
SARA Section 311/312 Hazard Classes Immediate (acute) health hazard Sudden release of pressure hazard 1,1,1,2-tetrafluoroethane (811-97-2)		
Sudden release of pressure hazard 1,1,1,2-tetrafluoroethane (811-97-2)		Immediate (acute) health hazard
	SARA Section 511/512 Hazard Classes	
	1,1,1,2-tetrafluoroethane (811-97-2)	
		ances Control Act) inventory
SARA Section 311/312 Hazard Classes Immediate (acute) health hazard	SARA Section 311/312 Hazard Classes	
Sudden release of pressure hazard		Sudden release of pressure hazard

15.2. International regulations

CANADA

TECH SELECT POE OIL CHARGE 6/4oz	
WHMIS Classification	Class A - Compressed Gas

EU-Regulations

No additional information available

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Classification according to Directive 67/548/EEC or 1999/45/EC

Not classified

15.2.2. National regulations

No additional information available

15.3. US State regulations

No additional information available

SECTION 16: Other information	
Indication of changes	: Revision - See : *.
Other information	: None.
Full text of H-phrases: see section 16:	
Compressed gas	Gases under pressure Compressed gas
H280	Contains gas under pressure; may explode if heated
NFPA health hazard	2 - Intense or continued exposure could cause temporary incapacitation or possible residual injury unless prompt medical attention is given.
NFPA fire hazard	: 1 - Must be preheated before ignition can occur.
NFPA reactivity	: 1 - Normally stable, but can become unstable at elevated temperatures and pressures or may react with water with some release of energy, but not violently.
HMIS III Rating	
Health	: 1 Slight Hazard - Irritation or minor reversible injury possible
Flammability	: 1 Slight Hazard
Physical	: 2 Moderate Hazard
SDS US (GHS HazCom 2012) - Technical Chemic	cal

The Supplier identified in Section 1 of this MSDS has evaluated this product and certifies it to be labeled and packaged in compliance with the applicable provisions of the Federal Hazardous Substance Act as stated in 16 CFR 1500 and enforced by the Consumer Product Safety Commission, and where applicable the products that require Child Resistant Closures are packaged in accordance with the Poison Prevention Packaging Act as stated in 16 CFR 1700 and enforced by the Consumer Product Safety Commission. All closures have been tested in accordance with the latest protocols. No other testing is required to certify compliance with the above. The date of manufacture is stamped on the product